

JSDZ0208



- Durable use
- Various Protections
- Three Opening Methods

Key Features

Tough

- Brushless Motor
- MCBF for Motor: 3 million times

Various Protections

- Infrared anti smashing
- Radar anti smashing
- Ground sensor-anti smashing
- Anti-collision arm
- Over Current Protection

Three Opening Methods

- Barrier arm opened by software
- Barrier arm opened by remote control
- Barrier arm opened by motor



THE WORLD'S LEADING SMART PARKING
SOLUTION PROVIDER

*Design and specification are subject to change without prior notice. All information was correct at time of print. All company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Shenzhen Jieshun Science and Technology Industry Co., Ltd. May 2019. All trademarks acknowledged.

SHENZHEN JIESHUN SCIENCE AND TECHNOLOGY INDUSTRY CO.,LTD.

• No 10, Longwei Road, Futian District, Shenzhen, 518049,China.
• en.jieshun.cn
• export@jieshun.cn
• +86-755-8311 2288



BRING SMART TO YOUR LIFE

BARRIER GATES



JSDZ0206B



- Light Perception Design
- Durable use
- Various Protections
- Three Opening Methods

Key Features

Light Perception Design

- P** P shape breathing light
- Ⓣ** LED light strip arm

Tough

- ⚙** Brushless Motor
- ⌚** MCBF for Motor: 3 million times

Various Protections

- 📡** Infrared anti smashing
- 📡** Radar anti smashing
- 👉** Ground sensor-anti smashing
- 🛑** Anti-collision arm
- ⚡** Over Current Protection

Three Opening Methods

- 📡** Barrier arm opened by software
- 📡** Barrier arm opened by remote control
- 📡** Barrier arm opened by motor

JSDZ0207B



- Light Perception Design
- Durable use
- Various Protections
- Three Opening Methods

Key Features

Light Perception Design

- P** Breathing Light Cover
- Ⓣ** LED light strip arm

Tough

- ⚙** Brushless Motor
- ⌚** MCBF for Motor: 3 million times

Various Protections

- 📡** Infrared anti smashing
- 📡** Radar anti smashing
- 👉** Ground sensor-anti smashing
- 🛑** Anti-collision arm
- ⚡** Over Current Protection

Three Opening Methods

- 📡** Barrier arm opened by software
- 📡** Barrier arm opened by remote control
- 📡** Barrier arm opened by motor

Specifications

Model Name	JSDZ0206B	JSDZ0207B	JSDZ0208
Power Supply	AC220±10%		
	AC110±10%		
Operating Temperature	-25 C ~70 C		
Relative Humidity	≤95%		
Motor Power	150W		
IP Rating	IP54		
Anti smashing	Infrared anti smashing , Radar anti smashing , Ground sensor anti smashing		
Anti collision arm	Support		/
Height of arm	930mm		
Dimension (L*W*H)	360×322×1125mm		370×330×1050mm
Straight Arm	Support	Support	Support
Folding Arm	Support	Support	Support
LED Arm	Support	Support	Support
Anti-smashing oval shape arm	Support	Support	/
Oval shape arm	Support	/	/

Available Barrier Arms

	Arm Type	Arm Length	Opening Period
Barrier Arm	Straight Arm	3≤L≤4m	0.8~2s
	Folding Arm	3≤L≤4m	1.5~2s
	LED Arm	3≤L≤4m	1.5~2s
	Anti-smashing oval shape arm	3≤L≤4m	2.5~4s
	Oval shape arm	3≤L≤6m	3~6s